

## VIEW™ | 4.3" Touchscreen

TL430 - 4.3" Touchscreen

**ClearOne**®

The TL430 is an IP-Based in-wall touch screen keypad featuring a high resolution, color LCD touch panel, designed to control a VIEW system. The TL430 features a 2-port Ethernet switch and two 4-pin Phoenix connectors for communications, power, and cascading one IP-Based Amplifier / Room Controller.



IP-BASED  
IN-WALL  
TOUCHSCREEN

### APPLICATIONS

- + Audio/Video Routing Control
- + Source Selection
- + Source Transportation
- + Audio Level Control
- + Control and Display of Camera Images
- + Multi-room System Control
- + HVAC Control
- + Lighting Controls
- + Control of Displays
- + Projection Screen / Projection Lift Control
- + Paging/Intercom

### ADVANTAGES

- + The VIEW TL430 uses a touch sensitive color LCD panel to display controls, metadata, and content. The TL430 includes a 4.3" TFT color LCD screen.
- + The TL430 interface allows control all aspects of a VIEW system, display metadata regarding the audio/video source or control system, and display images from IP cameras.
- + The intuitive user interface also allows the user to assume control over other zones or to control multiple zones.
- + "Skins" can be selected that blend the screen's look with the color and style of the room.
- + Supports over 15 languages and international language meta data.
- + Includes a built in microphone allowing for paging and zone monitoring over the VIEW network.
- + Included is a built in IR Receiver that recognizes all VIEW Discreet IR commands and support network IR passthrough of all other IR signals.
- + Each TL430 includes a white trim plate, but color kits (sold separately) are available in almond, ivory, and black.

The Power of AV over IP™

## &gt; TL430 - 4.3" REAR PANEL



## &gt; SPECIFICATIONS

**TL430 - 4.3" Diagonal LCD Touchscreen****Resolution**  
480 x 272**Viewing Angle**  
80° Horizontal  
80° Vertical**IR Control Sensor****Current**  
250 mA**Operating Temperature**  
23.87 BTU/hr**Connections**

Two (2) Ethernet RJ45 Port Switches

One (1) 4-pin Power In

Phoenix Connector

One (1) 4-pin Power Out

Phoenix Connector

**In-Wall Dimensions****(W x H x D)**  
4.75" x 3.8125" x 1.25"  
(120mm x 97mm x 32.2mm)**External Dimensions:****(W x H x D)**  
5.5" x 4.625" x 1.5625"  
(140mm x 117mm x 39.7mm)**Weight:**

0.8 lbs (0.363 kg)

**NetPower™**

1

**Compliance**

Restriction of use of certain

Hazardous Substances

(RoHS) compliant

CE

C-Tick

**Accessories**

TLB430 Rough-in Box

**Part Number**

TL430

Powered by StreamNet™

## &gt; CLEARONE LOCATIONS

**Headquarters:**  
**Salt Lake City, UT USA**  
5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116  
**Tel:** 801-975-7200  
**Toll Free:** 800-945-7730  
**Fax:** 801-977-0087  
sales@clearone.com**Latin America**  
**Tel:** 801-974-3621  
global@clearone.com**EMEA**  
**Tel:** 44 (0) 1189 036 053  
global@clearone.com**APAC**  
**Tel:** 801-303-3388  
global@clearone.com